



Product Specification Data

DCM VINYL-LIKE REMOVABLE

Facestock: Polyolefin Film

DCM Vinyl-Like is a mineral-reinforced, polyolefin-based synthetic paper. An excellent alternative to vinyl, DCM Vinyl-Like can be utilized for high temperature resistant tags and pressure sensitive applications. DCM Vinyl-Like is an excellent candidate for applications which require durability, strength, moisture / chemical / UV exposure, and where superior printing quality is required.

DCM Vinyl-Like is available in a variety of colors and thicknesses, including 3.2 mil White, 3.2 mil Matte Clear, 5.0 mil White.

Adhesive: Removable/Repositionable System

DCM Vinyl-Like features a water-based, removable/repositionable adhesive system designed to adhere to a multitude of smooth surfaces and remove cleanly without leaving any adhesive residue. DCM Vinyl-Like adhesive exhibits low initial tack, does not build over time, and removes cleanly from most any surface.

The minimum application temperature for DCM Vinyl-Like is +20°F, with a service temperature range of -10°F to +120°F.

Liner:

DCM 3.2 mil Vinyl-Like is stocked on 78# or 92# liner to suit your project's individual needs. DCM 5.0 mil Vinyl-Like is stocked on 92# liner.

	Stocked Liners				
	50#	78#	83#	92#	8 Pt.
Facestock: 3.2 White		X		X	
3.2 Clear		X		X	
5.0 White				X	

*Additional liners are available for custom orders. Please contact your DCM Sales Representative for details.

Item	Description
50# Liner	Semi-bleached, super-calendered, white kraft. (3.1 mil)
78# Liner	Clay-coated, super-calendered on one side, silicone-coated on clay-coated side. (4.6 mil)
83# Liner	Silicone liner, clay-coated on both sides. (5.8 mil)
92# Liner	Heavyweight, bleached, kraft, poly-coated on both sides. (7.1 mil)
8 Pt. Liner	White boardstock with printable backer. (8.0 mil)

Statement of Practical Use: Per industry standards, all pressure sensitive and non-pressure sensitive materials should be thoroughly tested under actual end-use conditions to ensure that it meets the requirements of the specific application. DCM, Inc. will make no warranty, expressed or implied, pertaining to the functionality or performance of this construction without end user validation, whereby the standard period of warranty will take effect, being one year from purchase date.

